PERRY TOWNSHIP MUSKINGUM COUNTY

PERMIT APPLICATION

INSTALLATION OF PRIVATE DRIVEWAYS AND APPROACHES (PRIVATE ACCESS TO A TOWNSHIP ROAD)

	(printed name of owner)
T 11	
To install a (size	diameter by
minimum length of culvert	to establish a private entrance.
The private entrance is loca	ted at
	on —
	he conditions, restrictions, and regulations of the Board of Trustees of Perry
-	I that the granting of this permit does not in any way abridge the rights of thurisdiction over township roads.
Board of Trustees in their ju	
Board of Trustees in their ju	urisdiction over township roads.
Board of Trustees in their ju	Approved by: Comments:
Board of Trustees in their ju Submitted by:	Approved by:
Board of Trustees in their ju Submitted by:	Approved by: Comments: Date:
Board of Trustees in their ju Submitted by:	Approved by: Comments: Date: Installation inspected by:
Board of Trustees in their justified by: Owner	Approved by: Comments: Date:
-	Approved by: Comments: Date: Installation inspected by:

PRIVATE DRIVEWAYS AND APPROACHES

I. RESPONSIBILITY

- A. Section 5543.16 of the Ohio Revised Code provides: "The owners of land shall construct and keep in repair all approaches or driveways from the public roads, under the direction of the Board of Trustees of Perry Township."
- B. All material, labor, and equipment necessary for construction and proper maintenance of driveways and approaches shall be furnished by property owner at his expense.
- C. If at any time the culvert ceases to function properly, it may be removed by township forces in order to ensure proper highway drainage.
- D. If, during road and ditch maintenance operations, the Township destroys the approach or driveway of any abutting property owner, it will be reconstructed by the Township.

II. DESIGN REGULATIONS

- A. Maintain minimum grade and develop drive profile to generally conform to shoulder contour. Drive and approach to be constructed to avoid wash-out of loose surface material and so that no surface water will be drained onto Township road.
- B. Culvert for drive shall be lain to line and grade of adjacent roadside ditch or as specified by the Board of Trustees of said Township.
- C. Pipe size shall be a minimum of 12 inch diameter by 20 feet long of as specified by the Board of Trustees of said Township.
- D. Recommend Pipe: Double Wall Plastic
- E. Cover over pipe will vary according to individual conditions, however a minimum of 12" is recommended.
- F. Headwall design shall be approved by the Board of Trustees of said Township.

